

Network Keyboard

KB-1100-E



Features


- Simple appearance and buttons layout, aesthetic and user-friendly.
- 4-inch display screen provides clear image with more details.
- 4D joystick for PTZ control (move up/down/left/right, focus, zoom).
- Uses Hoare joystick with high control precision and stability, effectively extending the lifetime.
- Power on/off button on the keyboard, convenient and energy-saving.
- Simple and clear keyboard configuration, easy for use and maintenance.
- Supports playing video on video wall and control video.
- Supports keyboard lock.
- Allows to set multiple-level user permissions.

Specifications

General	Description
Screen Size	4 inches
Joystick	4D joystick
Max Power Consumption (W)	<5
Product Dimensions (W*H*D) (mm)	345.00*189.82*128.16
Weight (kg)	1.2

Operating Temperature	-10° C to 55° C
Operating Humidity	10% to 90% RH, noncondensing
Other Interfaces	Description
Serial Port	1*RS232 (DB9, reserved) 2*RS485 (half-duplex, reserved)
Console	1*Console/RS485 shared interface (RJ45)
USB	2*USB (reserved)
Ethernet	1*RJ45, 10M/100M/1000M Based-T adaptive interface
Power	DC 12V
RST	1*Reset button

Dimensions



Interface



No.	Interface	Description
1	RS232	RS232 serial interface (reserved)
2	RS485	RS485 serial interface (reserved)
3	Console/RS485	1*Console/RS485 shared interface (RJ45)
4	USB	2*USB 2.0 interface (reserved)
5	Network	1*RJ45, 10M/100M/1000M Based-T adaptive interface
6	RST	1*Reset button
7	Power supply	DC 12V
8	Power switch	Power on/off

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.